

Specifications for RC Trailers Free Rider (RFR) High-Line Motorcycle Trailer

6 wide flat top low profile motorcycle trailer w/ 3000# idler axle

Available in 10, 12 and 14 foot lengths - Model code example: RFR6x12SA

Axle and tires

3000# 22 ½ degree up torsion idler axle (1)
ST205/75R15C (2) Radial tires on silver mod wheels

Frame

3 inch tube main frame
24 inch on center floor cross members
16 inch on center wall posts
24 inch on center roof bows
Painted and undercoated frame

Hitch and coupler

2" coupler w/ Safety chains
Breakaway kit safety system and 4 way flat plug for tow vehicle

Doors

Spring assisted ramp door w/ 2 vice locks
Beavertail at ramp entrance, entry level 4 inches lower than main floor
ATP transition flap inside
ATP on ramp door and flap
32" solid RV door curbside

Exterior

.030 exterior sheet metal with smooth sides (no visible fasteners).
Cast corners front and rear
24" brite anodized lower trim kit
ATP stone guard 24" tall w/ ATP tongue cover
Rear stabilizer jacks
2 - flo-through vents
Fiberglass cap
1 piece aluminum roof
1 pair LED striptail/brake lights w/ approved DOT exterior lighting

Interior

¾" plywood flooring
Marble linoleum overlay on main floor
ATP runners on main floor, ATP in rear area on main floor
1 - Chrome tubular removable wheel chock w/ 4 D rings
3/8" white interior walls
White vinyl ceiling
2 - 12V dome lights w/ wall switch

Standard dimensions

Interior height 65" on main floor, 69" in rear area (behind beavertail)
Exterior height 82"
Exterior widest point 90"
Inside wall to wall width 68"

Rear door opening width 63"

Rear door opening height 65" (including beavertail)

All dimensions based on standard model in this series. Please discuss with dealer any critical dimensions before ordering. An optional brake axle is available in this series, and may be required in some states. Please consult your dealer.