

Specifications for the RC Free Rider Motorcycle Trailer (RFREL) series
7 wide flat top low profile motorcycle trailer w/ 3500# brake axles
Standard model available in 12, 14 and 16 foot lengths. Wedge version also available on this model.
Standard model code example: RFREL7x16TA2

Axle and tires

3500# 22 ½ degree up torsion brake axles (2)
ST205/75D15C (2) bias tires

Frame

4 inch tube main frame
24 inch on center floor cross members
16 inch on center wall posts
24 inch on center roof bows
Painted and undercoated frame

Hitch and coupler

2 5/16" coupler
Safety chains
Breakaway kit safety system
7 way round plug for tow vehicle

Doors

Spring assisted ramp door w/ 2 vice locks
ATP transition flap inside
32" camlock door curbside w/ vice lock

Exterior

.030 exterior sheet metal
ATP stone guard 24" tall
Rear stabilizer jacks
2 - flo-through vents
Fiberglass cap
Galvanized roof
1 pair LED strip tail/brake lights
Approved DOT exterior lighting

Interior

¾" plywood flooring
3/8" plywood interior walls
2 – 12V dome lights w/ wall switch

Standard dimensions

Interior height 65"
Exterior height 82"
Exterior widest point 101"
Inside wall to wall width 80"
Rear door opening width 75"
Rear door opening height 61"

All dimensions based on standard model in this series. Please discuss with dealer any critical dimensions before ordering. An optional brake axle is available in this series, and may be required in some states. Please consult your dealer.