

Specifications for Royal Free Rider (RFR) High-Line Motorcycle Trailer

7 wide flat top low profile motorcycle trailer w/ 3500# brake axles

Standard model available in 12, 14 and 16 foot lengths. Wedge version also available in this model.

Standard model code example: RFR7x12TA2

Axle and tires

3500# Dexter EZ Lube 22 ½ degree up torsion idler axles (2)

ST205/75R15C (4) Radial tires on silver mod wheels

Frame

4 inch tube main frame

24 inch on center floor cross members

16 inch on center wall posts

24 inch on center roof bows

Painted and undercoated frame

Hitch and coupler

2 5/16" coupler w/ Safety chains

Breakaway kit safety system and 7 way round plug for tow vehicle

Doors

Spring assisted ramp door w/ 2 vice locks.

Beavertail at ramp entrance – entry level 4 inches lower than main floor

ATP transition flap inside

ATP on ramp door and flap

32" solid RV door curbside

Exterior

.030 exterior sheet metal w/ smooth sides (no visible fasteners)

Cast corners front and rear

24" brite anodized lower trim kit

ATP stone guard 24" tall w/ ATP tongue cover

Rear stabilizer jacks

2 - flo-through vents

Fiberglass cap

1 piece aluminum roof

1 pair LED strip tail/brake lights w/ approved DOT exterior lighting

Interior

¾" plywood flooring

Marble linoleum overlay on main floor

ATP runners on main floor, ATP in rear area on main floor

2 – Chrome tubular removable wheel chocks

3/8" white interior walls

White vinyl ceiling

8 D rings

2 – 12V dome lights w/ wall switch

Standard dimensions

Interior height 65" on main floor, 69" in rear area (behind beavertail)

Exterior height 82"

Exterior widest point 101"

Inside wall to wall width 80"
Rear door opening width 75"
Rear door opening height 65" (including beavertail)

All dimensions based on standard model in this series. Please discuss with dealer any critical dimensions before ordering.