

Specifications for RC Crown Series Gooseneck / 5th Wheel Race Trailer (RCSGN/FW) series

8 and 8 ½ wide flat top race trailers w/ 5200# axles

Available in 24, 26, 28, 30, 32, 34, and 36 foot lengths with standard tandem (TA) 5200# axles

Available in 38, 40, 42, 44, 46, 48, 50 and 53 foot lengths w/ standard triple (TR) 5200# axles

Call size includes bunk. Main floor approximately 8 feet shorter than call size.

Model code example: RCSGN/FW8.5x44TR52 – RCSGN/FW8.5x32TA3

Axles and tires

5200# Torsion brake axles w/ ST225/75R15D Radial tires

Frame

6 inch tube main frame

16 inch on center floor cross members

16 inch on center wall posts

16 inch on center roof bows

Painted and undercoated frame

Hitch and coupler

Gooseneck or 5th wheel style coupler w/ safety chains

Breakaway kit safety system w/ 7 way round plug for tow vehicle

Doors

Spring assisted ramp door w/ beavertail

Recessed camlocks on ramp door

48" camlock door curbside

Exterior

.030 exterior sheet metal

Brite front corners

Cast corners front and rear w/ brite wrap between front cast corners

Brite rear hoop

3 inch lower trim and 6 inch extruded top trim

ATP stone guard w/ ATP access door

One piece aluminum roof

Roof vent

1 pair LED recessed tail/brake lights

LED recessed clearance lights w/ approved DOT exterior lighting

Interior

¾" standard plywood flooring

3/8" plywood interior walls

White vinyl insulated ceiling

4 – D rings

3 – 12V dome lights w/ wall switch

Standard dimensions

Interior height 78"

Exterior height 105"

Exterior widest point 101"

Inside wall to wall width 90" (8 wides) - 96" (8 ½ wides)

Rear door opening width 84" (8wides) - 90" (8 ½ wides)

Rear door opening height 76"

Note: Dimensions listed are the same for 8 and 8 ½ wide models unless otherwise noted. All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81".

All dimensions based on standard model in this series. Models with heavier payload capacities and axle configurations are available. Please discuss with dealer any critical dimensions before ordering.