

Specifications for Crown Series STACKER Gooseneck / 5th Wheel Trailer (RCSGN/FW) series

8 ½ wide flat top trailer w/ 8000# triple axles

Available in 32, 34, 36, 38, 40, 42, 44, 46, 48, 50 and 53 foot lengths

Call size includes bunk. Main floor approximately 8 feet shorter than call size.

Model code example: RCSGN/FW8.5x48TR

These specs are for a maximum (54" extra) height unit. Other configurations available.

Axles and tires

8000# Dexter EZ Lube torsion brake axles

ST215/75R17.5H Radial tires

Frame

8 inch H beam main frame

16 inch on center floor cross members

16 inch on center NASCAR style wall posts

16 inch on center roof bows

Painted and undercoated frame

Hitch and coupler

Gooseneck or 5th wheel style coupler w/ safety chains

Breakaway kit safety system w/ 7 way round plug for tow vehicle

Doors

Spring assisted ramp door w/ beavertail and recessed camlocks on ramp door

48" camlock door curbside

Exterior

.050 exterior sheet metal

Cast corners front and rear

Brite front corners, brite front wrap between front cast corners, brite rear hoop

ATP stone guard w/ access door

One piece aluminum roof

3 inch aluminum lower exterior trim and 6 inch extruded aluminum top trim

1 pair LED tail/brake lights on ramp door

Recessed LED clearance lights w/ approved DOT exterior lighting

Interior

Hydraulic lift mechanism

¾" standard plywood flooring or ¾" treated plywood flooring

3/8" plywood interior walls

White vinyl insulated ceiling

4 – D rings

3 – 12V dome lights w/ wall switch

Standard dimensions

Interior height 132"

Exterior height 160"

Exterior widest point 101"

Inside wall to wall width 96"

Rear door opening width 95"

Rear door opening height 99" (w/ beavertail - includes 24" extra height on ramp door)

Note: All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81".

