

## **Specifications for Crown Series STACKER Gooseneck / 5<sup>th</sup> Wheel Trailer (RCSGN/FW) series**

### **8 ½ wide flat top trailer w/ 8000# triple axles**

Available in 32, 34, 36, 38, 40, 42, 44, 46, 48, 50 and 53 foot lengths

Call size includes bunk. Main floor approximately 8 feet shorter than call size.

Model code example: RCSGN/FW8.5x48TR

**These specs are for a maximum (54" extra) height unit. Other configurations available.**

### **Axles and tires**

8000# Torsion brake axles

ST215/75R17.5H Radial tires

### **Frame**

8 inch H beam main frame

16 inch on center floor cross members

16 inch on center NASCAR style wall posts

16 inch on center roof bows

Painted and undercoated frame

### **Hitch and coupler**

Gooseneck or 5<sup>th</sup> wheel style coupler w/ safety chains

Breakaway kit safety system w/ 7 way round plug for tow vehicle

### **Doors**

Spring assisted ramp door w/ beavertail and recessed camlocks on ramp door

48" camlock door curbside

### **Exterior**

.050 exterior sheet metal

Cast corners front and rear

Brite front corners, brite front wrap between front cast corners, brite rear hoop

ATP stone guard w/ access door

One piece aluminum roof

3 inch aluminum lower exterior trim and 6 inch extruded aluminum top trim

1 pair LED tail/brake lights on ramp door

Recessed LED clearance lights w/ approved DOT exterior lighting

### **Interior**

Hydraulic lift mechanism

¾" standard plywood flooring or ¾" treated plywood flooring

3/8" plywood interior walls

White vinyl insulated ceiling

4 – D rings

3 – 12V dome lights w/ wall switch

### **Standard dimensions**

Interior height 132"

Exterior height 160"

Exterior widest point 101"

Inside wall to wall width 96"

Rear door opening width 95"

Rear door opening height 99" (w/ beavertail - includes 24" extra height on ramp door)

**Note: All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81".**

