

## **Specifications for RC Crown Series Race Trailer (RCS)**

### **8 and 8 ½ wide flat top race trailers w/ 5200# axles**

Available in 18, 20, 22, 24, 26, 28, 30, 32 and 34 foot lengths

Model code example: RCS8.5x28TA3

### **Axles and tires**

5200# Torsion brake axles (2)

ST225/75R15D (4) Radial tires

### **Frame**

6 inch tube main frame

16 inch on center floor cross members

16 inch on center wall posts

16 inch on center roof bows

Painted and undercoated frame

### **Hitch and coupler**

2 5/16" coupler w/ Safety chains and 3<sup>rd</sup> member tongue

Breakaway kit safety system w/ 7 way round plug for tow vehicle

### **Doors**

Spring assisted ramp door w/ beavertail

Recessed camlocks on ramp door

48" camlock door curbside

### **Exterior**

.030 exterior sheet metal

Brite front corners

Cast corners front and rear w/ brite wrap between front cast corners

Brite rear hoop

3 inch lower trim

6 inch extruded top trim

ATP stone guard 24" tall

One piece aluminum roof

Roof vent

1 pair LED recessed tail/brake lights

LED recessed clearance lights

Approved DOT exterior lighting

### **Interior**

¾" standard plywood flooring

3/8" plywood interior walls

White vinyl insulated ceiling

4 – D rings in car position. 9 rope ties shipped loose.

3 – 12V dome lights w/ wall switch

### **Standard dimensions**

Interior height 78"

Exterior height 110" (including roof vent)

Exterior widest point 101"

Inside wall to wall width 90" (8 wides) - 96" (8 ½ wides)

Rear door opening width 84" (8wides) - 90" (8 ½ wides)

Rear door opening height 76" (w/ beavertail)

**Note: Dimensions listed are the same for 8 and 8 ½ wide models unless otherwise noted. All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81”.**

**All dimensions based on standard model in this series. Models with heavier payload capacities and axle configurations are available. Please discuss with dealer any critical dimensions before ordering.**