

Specifications for Crown Series STACKER tag trailer (RCS) series 8 ½ wide flat top race trailer w/ 8000# triple axles

Available in 24, 26, 28, 30, 32, 34 and 36 foot lengths

Model code example: RCS8.5x32TR80

These specs are for a maximum (54") extra height unit. Other configurations are available.

Axles and tires

8000# Torsion brake axles (2)

ST215/75R17.5H Radial tires

Frame

8 inch H beam main frame

16 inch on center floor cross members

16 inch on center NASCAR style wall posts

16 inch on center roof bows

Painted and undercoated frame

Hitch and coupler

2 5/16" coupler w/ Safety chains and 3rd member tongue

Breakaway kit safety system w/ 7 way round plug for tow vehicle

Doors

Spring assisted ramp door w/ beavertail and recessed camlocks on ramp door

48" camlock door curbside

Exterior

.050 exterior sheet metal

Brite front corners

Cast corners front and rear w/ brite wrap between front cast corners and brite rear hoop

3 inch lower trim

6 inch extruded top trim

ATP stone guard 24" tall

One piece aluminum roof

Roof vent

1 pair LED recessed tail/brake lights

LED recessed clearance lights w/ approved DOT exterior lighting

Interior

Hydraulic lift mechanism

¾" standard plywood flooring or ¾" treated plywood

3/8" plywood interior walls

White vinyl insulated ceiling

4 – D rings in car position.

3 – 12V dome lights w/ wall switch

Standard dimensions

Interior height 132"

Exterior height 160"

Exterior widest point 101"

Inside wall to wall width 96"

Rear door opening width 90"

Rear door opening height 99" (w/ beavertail – includes 24" extra height on ramp door)

Note: All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81".

