

# **Specifications for the RC Spring Trailer Car Hauler (RSTCH) series 8 ½ wide round top trailer w/ tandem 3500 # axles**

Available in 16, 18, 20, 22, and 24 foot lengths  
Model code example: RSTCH8.5x24TA2

## **Axles and tires**

3500# Spring brake axles (2)  
ST205/75R15C (4) Radial tires

## **Frame**

6 inch tube main frame  
3<sup>rd</sup> member tongue  
16 inch on center floor cross members  
16 inch on center wall posts  
24 inch on center roof bows  
Painted and undercoated frame

## **Hitch and coupler**

2 5/16" coupler  
Safety chains  
Breakaway kit safety system  
7 way round plug for tow vehicle

## **Doors**

Spring assisted beavertail ramp door w/ flap  
48" camlock door curbside

## **Exterior**

.030 exterior sheet metal  
Brite front corners  
ATP stone guard 24" tall  
Roof vent  
Fiberglass cap  
Galvanized roof  
1 pair seal beam recessed tail/brake lights  
Approved DOT exterior lighting

## **Interior**

¾" plywood flooring  
3/8" plywood interior walls  
4 – D rings  
2 – 12V dome lights w/ wall switch

## **Standard dimensions**

Interior height 78"  
Exterior height 110" (including roof vent)  
Exterior widest point 101"  
Inside wall to wall width 90" (8 wides) – 96" (8 ½ wides)  
Rear door opening width 84" (8 wides) – 90" (8 ½ wides)  
Rear door opening height 76" (including beavertail)

**Note: Dimensions listed are the same for 8 and 8 ½ wide models unless otherwise noted. All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81”.**

**All dimensions based on standard model in this series. Please discuss with dealer any critical dimensions before ordering.**