

Specifications for Royal Gooseneck / 5th Wheel (RTTGN/FW) series 8 and 8 ½ wide round top trailers w/ 3500# torsion axles

Available in 22, 24, and 26 foot lengths w/ standard tandem (TA) 3500# axles

Call size includes bunk. Main floor approximately 8 feet shorter than call size.

Model code example: RTTGN/FW8.5x24TA2

Axles and tires

3500# Dexter EZ Lube torsion brake axles

ST205/75R15C Radial tires

Frame

6 inch tube main frame

Gooseneck or 5th wheel style coupler

16 inch on center floor cross members

16 inch on center wall posts

24 inch on center roof bows

Painted and undercoated frame

Hitch and coupler

Gooseneck or 5th wheel style coupler

Safety chains

Breakaway kit safety system

7 way round plug for tow vehicle

Doors

Double rear doors

48" camlock door curbside

Exterior

.030 exterior sheet metal

ATP stone guard w/ access door

Fiberglass cap

Galvanized roof

2 pairs seal beam recessed tail/brake lights

Approved DOT exterior lighting

Interior

¾" plywood flooring

3/8" plywood interior walls

2 – 12V dome lights w/ wall switch

Standard dimensions

Interior height 78"

Exterior height 105"

Exterior widest point 101"

Inside wall to wall width 90" (8 wides) – 96" (8 ½ wides)

Rear door opening width 84" (8 wides) – 90" (8 ½ wides)

Rear door opening height 72"

Note: Dimensions listed are the same for 8 and 8 ½ wide models unless otherwise noted. All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81".

All dimensions based on standard model in this series. Please discuss with dealer any critical dimensions before ordering.