

## **Specifications for RC Gooseneck / 5<sup>th</sup> Wheel (RTTGN/FW) series 8 and 8 ½ wide round top trailers w/ 5200# torsion axles**

Available in 22, 24, 26, 28, 30, 32, 34 and 36 foot lengths w/ standard tandem (TA) 5200# axles

Available in 38, 40, 42, 44, 46, 48, 50 and 53 foot lengths w/ standard triple (TR) 5200# axles

Call size includes bunk. Main floor approximately 8 feet shorter than call size.

Model code examples: RTTGN/FW8.5x32TA3 – RTTGN/FW8.5x44TR52

### **Axles and tires**

5200# Torsion brake axles

ST225/75R15D Radial tires

### **Frame**

6 inch tube main frame

Gooseneck or 5<sup>th</sup> wheel style coupler

16 inch on center floor cross members

16 inch on center wall posts

24 inch on center roof bows

Painted and undercoated frame

### **Hitch and coupler**

Gooseneck or 5<sup>th</sup> wheel style coupler

Safety chains

Breakaway kit safety system

7 way round plug for tow vehicle

### **Doors**

Double rear doors

48" camlock door curbside

### **Exterior**

.030 exterior sheet metal

ATP stone guard w/ access door

Fiberglass cap

Galvanized roof

2 pairs seal beam recessed tail/brake lights

Approved DOT exterior lighting

### **Interior**

¾" plywood flooring

3/8" plywood interior walls

2 – 12V dome lights w/ wall switch

### **Standard dimensions**

Interior height 78"

Exterior height 105"

Exterior widest point 101"

Inside wall to wall width 90" (8 wides) – 96" (8 ½ wides)

Rear door opening width 84" (8 wides) – 90" (8 ½ wides)

Rear door opening height 72"

**Note: Dimensions listed are the same for 8 and 8 ½ wide models unless otherwise noted. All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81".**

**Other models with heavier rated axles and more payload capacity are available. Please consult your dealer.**

**All dimensions based on standard model in this series. Please discuss with dealer any critical dimensions before ordering.**