

## **Specifications for the RC Spring Trailer Tandem Axle (RST) series 8 and 8 ½ wide round top cargo trailer w/ 5200 # axles**

Available in 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30 and 32 foot lengths

Model code example: RST8x16TA3 / RST8.5x16TA3

### **Axles and tires**

5200# Spring brake axles (2)

ST225/75R15D (4) Radial tires

### **Frame**

6 inch tube main frame

3<sup>rd</sup> member tongue

16 inch on center floor cross members

16 inch on center wall posts

24 inch on center roof bows

Painted and undercoated frame

### **Hitch and coupler**

2 5/16" coupler

Safety chains

Breakaway kit safety system

7 way round plug for tow vehicle

### **Doors**

Double rear doors

36" camlock door curbside on 10, 12, 14, 16 and 18 foot models

48" camlock door curbside on 20, 22 and 24 foot models

### **Exterior**

.030 exterior sheet metal

ATP stone guard 24" tall

Fiberglass cap

Galvanized roof

1 pair seal beam recessed tail/brake lights

Approved DOT exterior lighting

### **Interior**

¾" plywood flooring

¼" brown luan interior walls

2 – 12V dome lights w/ wall switch

### **Standard dimensions**

Interior height 78"

Exterior height 105"

Exterior widest point 101"

Inside wall to wall width 90" (8 wides) – 96" (8 ½ wides)

Rear door opening width 84" (8 wides) – 90" (8 ½ wides)

Rear door opening height 72"

**Note: Dimensions listed are the same for 8 and 8 ½ wide models unless otherwise noted. All models in this series have wheel boxes inside unit. The distance between wheel boxes on all models is 81".**

**All dimensions based on standard model in this series. Please discuss with dealer any critical dimensions before ordering.**